LUBRICANTS

CHAIN LUBE



CHAIN LUBE

Klotz Hi-Performance Chain Lube contains EXTRATAC™ Anti-Wear System for all street, off-road, and racing applications. Specially formulated for conventional and "O" ring type roller chains to provide the maximum level of lubrication and rust protection for all types of competition. Klotz EXTRATAC Anti-Wear System penetrates deeply to displace moisture and dirt maximum corrosion protection.

- EXTRATAC penetrates deeply and dries tacky
- Waterproof formula prevents rust and wash off
- Approved for conventional and "O" ring chains
- Extends chain and sprocket life
- Loosens stiff chain links
- Environmentally safe formula

APPLICATION:

Motorcycle/ATV Kart/Micro Sprint

► CHARACTERISTICS:

Film Strength: 8 1=failure; 10=virtually no wear Viscosity @ 100°F: 600 SUS @ 40°C: 150 cSt

Pour Point: N/A Flash Point: 380°F Color: Green





▶ DIRECTIONS:

Compatibility: Will blend with petroleum oils and synthetic lubricants. 60% Biodegradable formula.

For best results, preheat chain with a 5 minute ride. Wash and clean all chain and sprocket surfaces before applying Chain Lube. Shake can well. Rotate wheel and apply a liberal bead along inside surface of chain. Allow Chain Lube to penetrate rollers and dry for 10 minutes, then wipe off excess lube.

AVAILABILITY: KL-605 15.5 oz aerosol