



SYNTHETIC ENGINE LUBRICANT

SideXSide Synthetic Lubricant 15W/50

- Recommended for Arctic Cat, Can-Am, Honda, Kawasaki, Kymco, Suzuki, Polaris and Yamaha side-by-side applications
- Certified warranty compliant: JASO MA2, API SJ-SN
- Designed for wet clutch integrated transmission
- Developed for extreme loading stresses of off-road use
- Provides smoother, quieter clutch and transmission operation



CHARACTERISTICS

Pour Point -29°F
Flash Point 480°F
Maximum RPM N/A
Viscosity @ 100°C 16.30 cSt Min 21.90 cSt Max **19.20 cSt Typical**
Product Color Red
Chemical 100% Pure Synthetic

CERTIFICATIONS

API SJ-SN, JASO MA2

DIRECTIONS

Fill crankcase to manufacturer's recommended level. Change engine as manufacturer recommends or when it becomes discolored with engine contaminants.

COMPATIBILITY

Compatible with conventional engine oils and most synthetics.

PART NUMBERS

KL-806	10 QT CASE
KL-806 30 GL	30 GALLON DRUM
KL-806 55 GL	55 GALLON DRUM

RECOMMENDED APPLICATIONS

4-Stroke SideXSide:
Off-Road Racing
Trail Riding

Klotz Synthetic Lubricants
Fort Wayne, IN USA

Order Online: at klotzlube.com
Tech Line: 260.490.0489

Order Line: 800.242.0489
Email: salesteam@klotzlube.com

©2018 Klotz S.L., Inc Tech Sheet